



POWER RP 150DW RUST PREVENTIVE OIL

POWER RP 150DW is well-formulated water displacement type thin film rust preventive oil designed to provide protection to steel components against high humidity & extreme corrosive environment. It effectively displaces moisture and protects the surface by arresting rust and corrosion.

PROTECTION OF TREATED PARTS: Indoors - 3 to 6 months
Outdoors - 1 to 2 months

CHARACTERISTICS	POWER RP 150DW
Appearance	Clear brown liquid
Specific gravity @ 29.5°C	0.82 – 0.85
Type of film	Oily, smooth
Flash point COC, °C, min	40
Film Thickness (microns)	4.5
Salt Spray Test – ASTM B-117(Hrs)	72
Water displacement test	Pass

APPLICATION:

- **POWER RP DW-150** is recommended for protection of parts coming from machines using water-soluble oils and synthetic oils as coolants.
- Also recommended for industries manufacturing nuts, bolts, HSS bearings, Steel tubes, bars, tool-bits, tools and other small components for in-process protection.

PERFORMANCE BENEFITS:

- Effective and efficient corrosion protection (to small cast iron parts also)
- Cost effective due to high coverage
- Easy removal of film with kerosene or any other petroleum solvent

(Version # 1 April 14th 2008)

Disclaimer: APAR makes no warranties, representation or conditions of any kind expressed or implied for use with respect to these products. Final determination of suitability of the products for the application contemplated by the user is solely their responsibility.